



Artiglio Master JOLLY

the heart of the “Leva la Leva” technology



DYNAMIC BEAD BREAKING DEVICE with dual specular bead breaker disc. The radial positioning of the discs is made easier by an automatism that is able to prevent any manual positioning

by the operator. **CONTROLLED PENETRATION** (Patent Pending) Precision, rapidity and repeatability are guaranteed by the patented bead breaking system and by the perfectly synchronized and symmetrical motions of the two discs.

TECHNICAL DATA

Rim diameter	12" ÷ 26"
Maximum tyre diameter	1100 mm
Maximum tyre width	360 mm (14")
Rotation torque	1100 Nm
Rotation speed	7 rpm-20 rpm
Bead breaker	
Maximum opening	18"
Shoe force	7600 N
Power supply	electric 1Ph 230V - 0,98 kW 50 Hz electric 1Ph (alternative) 110V - 0,98 kW 60 Hz
Operating pressure	8-9,5 bar
Weight	400 kg
Dimensions l x d x h	1134 x 1904 x 1814 mm


STANDARD ACCESSORIES



ACCESSORIES ON REQUEST



801260961 T.I. kit



8-11100087 Universal flange for special rims



8-11100039 Reverse rim universal flange



0-51100502 TPM-02 Device for checking operation of TPMS sensors