




# EM9580 LaserLine



Electronic wheel balancer with display.  
Rapid and precise, ideal for high work loads.

## TECHNICAL DATA

Power supply voltage	115/230 V - 1ph - 50/60 Hz
Total power absorption	400 W
Balancing speed	75 - 85 - 98 rpm
Max. unbalance value	999 g 35,3 oz
Resolution	1 g
Average measurement time	(14 kg wheel) 5,5 s
Shaft diameter	40 mm
Rim width setting range	1,5" ÷ 20"
Rim diameter setting range	1" ÷ 35"
Rim diameter measurement range	10" ÷ 28"
Maximum wheel width (with guard)	600 mm
Maximum wheel diameter (with guard)	1118 mm
Maximum wheel/machine distance	275 mm
Maximum wheel weight	75 Kg
Machine weight	140 kg
Maximum dimensions l x d x h	1453 x 894 x 1858



New electromechanical system which reduces working times and increases centring precision (**EM9580 C**), or manual wheel clamping with quick ring (**EM9580**).

## STANDARD ACCESSORIES EM9580 C

## AUTOMATIC LOCKING SYSTEM




## STANDARD ACCESSORIES EM9580

## MANUAL LOCKING SYSTEM



## RECOMMENDED ACCESSORIES



8-21100141

**DX/CBF** Centring accessory for van and off-road wheels with central hole with  $\varnothing 117 \div 173$  mm




8-21100091

**FRU** Universal self-centring flange for wheels with or without central hole, hole  $\varnothing$  min. 90 max. 210 mm



8-21100230

**TT-0** "Wiegthless effect" wheel lifter




8-21100235

LCD Monitor 19"

8-21100234

LCD Monitor 22"



8-21100232

**AWD** automatic sensor