

# A9824TI-1500

## SERIES PASSENGER, LIGHT TRUCK TIRE CHANGERS

Superior quality teamed with a sleek design and other unique features allow this machine to achieve speeds up to 50% faster than any other tire changer on the market in its price range. That's why Corghi was awarded ISO 9001 Quality Certification, industry's most coveted award. Runflat certified by all major tire manufacturers.

# 24''



### Same features as the A9824TI **PLUS PU1500 POWER ASSIST UNIT**

- Pneumatic powered
- Wheel and bead pressing arm
- Bead lifter
- Maintains bead in drop center
- Eliminates bead stress
- Eliminates wheel damage
- One person operation to change even the most difficult tires
- PAX capable with PAX kit
- Rim clamping assist
- Shipping weight 829 lbs.

# A9824TI



## Features

- Built-in table inflator with jets in the jaws
- Unique mount/demount head does not touch the rim during operation.
- Locking handle locks head away from the rim.
- Powerful action bead-breaker blade follows bead to inside rim contour.
- Heavy-duty turntable rotates in either direction.
- Rebuildable stainless steel cylinders.
- Heavy-duty stainless steel turntable.
- Safe, fast, profitable and affordable.
- Bead-pressing lever
- Upper arm assembly swings out-of-way.
- Shipping weight 608 lbs.
- Also available with air motor.

## Standard Accessories

- Lube Bucket
- Lube Brush
- Tire Lever
- Tire Lever Covers
- Set of Jaw Protectors
- M/D Head Bottom Inserts
- Set of Inserts
- Air Tank Gauge Assembly
- B/B Blade Protector on Machine
- Bead Pressing Lever on Machine

## Specifications

• <u>Ext. Rim Size</u>	<u>10"-24"</u>
• <u>Optional w/Adapter</u>	<u>8"-28"</u>
• <u>Int. Rim Size</u>	<u>13"-26"</u>
• <u>Voltage</u>	<u>110V 1 Ph or Air</u>
• <u>Rim Width</u>	<u>3.5"-14"</u>
• <u>Max. Tire Diameter</u>	<u>47"</u>
• <u>Air Pressure</u>	<u>150psi</u>
• <u>Bead Breaker Power @ Shoe</u>	<u>3500lbs</u>
• <u>Torque</u>	<u>737ft/lbs</u>

## Limited Warranty

- 10 Years on Transmission
- 1 Year on Parts and Labor

 <https://www.facebook.com/corghiau>

