



**No
Contact**
with the rim

**Innovative
Design**
for wheel quick
positioning



**Reliable
and fast
clamping**
thanks to the
innovative coupling
mechanism



FEATURES

- **Fastening to the wheel:** no contact with the rim to prevent any damage.
- **Quick:** quick lever-operated mounting and demounting, without toothed gears.
- **Self-centering:** the synchronous opening and closing mechanism allows the central pin to be always aligned with wheel centre. The rollers integrated inside jaws allow greater smoothness and mounting ease.
- **Runout:** suitable for thrust compensation procedure of 3D aligners (*).
- **Lightweight and ergonomic:** the innovative design and low weight make it easy to handle and operate.

* Refer to the wheel aligner catalogue to check for compatibility.

OPTIONAL ACCESSORIES



Clamp holder multi-purpose trolley and additional jaws



Clamp holder set for wall mounting with support for additional jaws



Set of XL extensions for wheel diameter from 32" to 39"



Extension set for use with vans

TECHNICAL SPECIFICATIONS

Compatibility	3D aligners (*)
Wheel diameter	19" to 39"
Rim diameter	10" to 30"

Wheel arch protection included.

The set of supplied extensible jaws allows working on wheel diameter from 19" to 32".

* Refer to the wheel aligner catalogue to check for compatibility.

The manufacturer reserves the right to modify the features of its products at any time.